



Home > Equipment > Trenchers > RT200

## RT200 Specs

General Dimensions and Weights		
Length (Tractor with Tires)	79"	200.66 cm
Width	37.5"	95.25 cm
Width (Over Rubber Tires)	37.5"	95.25 cm
Height	44"	111.76 cm
Weight (Tractor with Tires)	1380 lbs	625.96 kg
Wheel Base From Centerline of Axles	46"	116.84 cm
Tread Width with Rubber Tires (Centerline to Centerline)	27.5"	69.85 cm

Engine Option One		
Make and Model	Kohler Command CH-23	
Fuel Type	Gas	
Gross Horsepower	23 hp	17.15 kw
Horsepower at Maximum RPM (Gross)	23 hp	17.15 kw
Displacement	41 cu-in	.67 L
Number of Cylinders	2	
Cooling Medium	Air	
Aspiration	Natural	
Maximum Operating Angle (Fore/Aft)*	25 deg	

<b>Maximum Operating Angle (Left/Right)*</b>	25 deg	
--	--------	--

<b>Capacities</b>		
<b>Fuel Tank</b>	5.2 gal	19.71 L
<b>Hydraulic Tank</b>	8 gal	30.28 L
<b>Hydraulic System</b>	8.5 gal	32.22 L
<b>Engine Oil</b>	0.5 gal	1.9 L

<b>Hydraulic System</b>		
<b>Attachment Pump Relief Pressure (Trencher/Forward)</b>	2300 psi	158.58 bar
<b>Ground Drive Pump Relief Pressure Forward/Reverse</b>	1740 psi	119.97 bar
<b>Ground Drive Pump gpm at Maximum Engine RPM</b>	9.5 gpm	36.01 L/min
<b>Hydraulic Supply Filter Rating</b>	3 micron	
<b>Attachment Pump gpm at Maximum Engine RPM</b>	18.75 gpm	71.06 L/min
<b>Hydraulic Return Filter Rating</b>	3 micron	

<b>Ground Drive</b>		
<b>Ground Drive Type</b>	Hydrostatic	
<b>Clutch Type</b>	Electromagnetic	
<b>Maximum Forward Transport Speed at Full Throttle</b>	2.39 mph	3.85 km/h
<b>Maximum Reverse Transport Speed at Full Throttle</b>	0.95 mph	1.53 km/h

## ATTACHMENTS

